




Superior  
Manufacturing  
Group, Inc.

# 035 Skate-Spike Matting™

Specialty Matting

Available Colors: Black



Specialty



**S**kate-Spike Matting™ is a durable vinyl linear ribbed top surface that minimizes damage to floors from spikes or skates. Intended for use in skating rinks, locker rooms, and gymnasiums.

Test	Test Description	*Results
Compression Deflection	Test specimen is subjected to varying compression load levels and the resulting deflection was measured. The greater the deflection, the better the anti-fatigue properties. (Inches)	N/A
Coefficient of Friction ASTM C1028-96	A neolite heel assembly with a predetermined load is pulled horizontally with a dynamometer to measure the force required to cause the assembly to slip.	.68
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions. Results measured in Weight loss (Grams)	0.37 Grams
Elongation ASTM D412	Test specimen is stretched at a specified rate until breaking point. The results are measured in weight needed to break, and % of size increase at breaking point.	150%
Hardness ASTM D2240-02	The hardness of a test sample is measured by means of a type A Shore Durometer. It measures the penetration of its specified indenter forced into the material under specified conditions	88

\*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.



Custom Lengths

- Available in 3' x 75' roll
- Thickness: 1/4"
- Weight: 1.5 lbs/per sq. ft.

