




Superior
Manufacturing
Group, Inc.

543 Cushion-Tred™ Anti-Fatigue/Anti-Slip Matting



Available Colors: Black, Red

Good Better Best Superior



Cushion-Tred™ is made from a resilient rubber compound that can withstand many of the commonly found industrial chemicals, cutting fluids, oils, and greases. A large hole drainage system facilitates the removal of liquid and debris from the work area. Multiple mats can be affixed together with optional connector strips, and the modular design is compatible with the NoTrax® M.D. Ramp System for on-site custom configurations.

Test	Test Description	*Results
Compression Deflection	Test specimen is subjected to varying compression load levels and the resulting deflection was measured. The greater the deflection, the better the anti-fatigue properties. (Inches)	.703" (40 lbs/sq. inch)
Coefficient of Friction ASTM C1028-96	A neolite heel assembly with a predetermined load is pulled horizontally with a dynamometer to measure the force required to cause the assembly to slip.	.75
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions. Results measured in Weight loss (Grams)	(data currently unavailable)
Elongation ASTM D412	Test specimen is stretched at a specified rate until breaking point. The results are measured in weight needed to break, and % of size increase at breaking point.	94.2% (average of 5 specimens)
Hardness ASTM D2240-02	The hardness of a test sample is measured by means of a type A Shore Durometer. It measures the penetration of its specified indenter forced into the material under specified conditions	63

*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.



Anti-Fatigue



Food Processing



Anti-Slip



Drainage



Welding



Food Service

- Available in two versions:
 - Black: NBR (Natural Rubber) - grease resistant w/1 year warranty
 - Red: Nitrile Rubber - grease proof w/5 year warranty
- Thickness: 7/8"
- Stock Sizes: 2' x 3', 3' x 3', 3' x 5'
- Compatible with patented 551 MD Ramp System



RESULTS from INDEPENDENT TEST LABS & PRESENTED as COMPARISONS to OTHER NoTRAX® INDUSTRIAL MATS