



Superior
Manufacturing
Group, Inc.

826 Diamond Stat™ Dissipative/Anti-Static Matting



Available Colors: Black

Good Better Best Superior



Dissipative/anti-static matting is designed to absorb static electricity. Simple worker tasks such as walking, or even sitting on certain types of stools create static electricity. If left unchecked, static will pass from the worker to sensitive equipment potentially damaging computer chips and electric circuitry. This mat drains the static electric charge from the worker thereby safeguarding the equipment.

Test	Specifications	*Results
Static Dissipation	Decay Rate (15,000 to 500kv) in seconds	Std. 826 without grounding strap - 2.68 Std. 826 with grounding strap - 1.32

*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.



- Utilizes NoTrax® exclusive UniFusion™ bond
- Top surface is a diamond deck-plate vinyl compound bonded to a dense closed cell foam base
- Beveled edges on 4 sides
- Grommet inset for recommended grounding cord
- Resistivity: 10⁷ ohms
- Thickness: 9/16"
- Weight: 1.36 lbs per sq./ft.
- Stock Sizes: 2' x 3', 3' x 5', 3' x 12'
- Roll Sizes: 3' x 75'
- Custom Sizes: 3' width to 75' length



Anti-Static



Anti-Fatigue



Custom Lengths



RESULTS FROM INDEPENDENT TEST LABS & PRESENTED AS COMPARISONS TO OTHER NoTRAX® FOOD SERVICE MATS